## **Amendments to the Claims**

- 1 1. (currently amended) A method for encoding an inter-frame of a
- 2 compressed video, the inter-frame including a plurality of macroblocks in a
- 3 predetermined order, each macroblock having an associated motion vector,
- 4 comprising:
- 5 identifying, for each current macroblock in the predetermined order, a
- 6 set of near macroblocks;
- 7 assigning an index to each near macroblock;
- 8 determining a difference between the motion vector of the current
- 9 macroblock and the motion vector of each near macroblocks;
- sorting the indices of the near macroblocks in order of the differences;
- appending the sorted indices to the inter-frame, in which the sorted
- indices are identified by a separation code in the inter-frame.
  - 1 2. (original) The method of claim 1, in which the set of near macroblocks are
- 2 immediately adjacent to the current macroblock.
- 1 3. (original) The method of claim 2, in which macroblocks immediately
- 2 adjacent to the set of near macroblocks are included in the set.
- 4. (original) The method of claim 1, in which the order is a raster scan order.
- 5. (original) The method of claim 1, in which the difference is in terms of a
- 2 mean squared error.

- 1 6. (original) The method of claim 1, in which the difference is in terms of an
- 2 absolute error.
  - 7. (canceled)
- 1 8. (original) The method of claim 1, further comprising:
- 2 transmitting the inter-frame through a noisy channel;
- decoding the transmitted inter-frame;
- 4 detecting a lost macroblock in the decoded inter-frame;
- 5 reading the sorted indices corresponding the lost macroblock;
- 6 concealing the lost macroblock by one of the motion vectors identified
- 7 in the sorted indices.
- 9. (original) The method of claim 8, in which the one motion vector is a
- 2 received motion vector with a smallest difference to the motion vector of the
- 3 lost macroblock.
- 1 10. (original) The method of claim 1, in which macroblocks along edges of
- 2 the inter-frame are replicated adjacently on an outside of the inter-frame to
- 3 facilitate processing of edge blocks of the current macroblock.